

PERFORMANCE

Revised May 2026



PROTECTIVE CLOTHING

minimum requirements

	Driver / Rider Suit				Gloves			Shoes/Boots			Socks	Balaclava	Underwear
	SFI 3.2A/5 or FIA 8856-2000	SFI 3.2A/15	SFI 3.2A/20	Full leather and 1 piece; or full leather and 2 piece and zipped together.	SFI 3.3/5 or FIA 8856-2000	SFI 3.3/15	Leather motorcycle riding type, with cuff wrist closure. Gloves and jacket sleeves must overlap by a minimum of 50mm.	SFI 3.3/5 or FIA 8856-2000	SFI 3.3/15	Purpose built motorcycle riding boots. May use short boots that cover ankles if pants cover top of boots. Elastic sided boots prohibited, lace up or zip up.	SFI 3.3 or FIA 8856-2000	SFI 3.3 or FIA 8856-2000 or Helmet Skirt 3.3	SFI 3.3 or FIA 8856-2000
Performance Supercharged enclosed composite body.													
Sportsman Supercharged enclosed Steel Body OEM Firewall													
Performance Supercharged Steel Bodied with fabricated firewall													
Performance Supercharged Dragster Rear Engine													
Performance Supercharged Dragster Front Engine													
Performance Supercharged Altered													
Performance Naturally Aspirated Vehicles													
Performance Bike													

Minimum Requirement

Optional However Recommended

SUPERCHARGING DEFINITION *Blower, Nitromethane, Turbocharger, Nitrous oxide injection*

Revised: May 2026

PERFORMANCE CATEGORY = Competition Eliminator - Performance Bike - Super Stock - Super Compact